




Features

- 1.2 dB Slope
- Negative Insertion Loss Slope vs. Frequency
- Wideband operation, DC to 6 GHz
- Excellent Power Handling Capability
- Small Size and simple to use (2 mm x 2 mm)
- Human Body Model (HBM): Class 2 (Pass 2000V)



TOP VIEW



Applications

- Cellular
- PCS
- Communications
- Radar
- Defense

Electrical specifications at 25°C

Parameter	Condition (GHz)	Min.	Typ.	Max.	Units
Frequency Range		DC		6	GHz
Insertion Loss	0.01	1.1	1.7	1.8	dB
	1	-	1.55	-	
	2	-	1.25	-	
	3	0.6	1	1.35	
	4	-	0.8	-	
	5	-	0.75	-	
VSWR	6	0.3	0.65	0.9	:1
	0.01-1	-	1.08	-	
	1-2	-	1.12	-	
	2-3	-	1.12	-	
	3-4	-	1.18	-	
	4-5	-	1.38	-	
Input RF Power	5-6	-	1.58	-	dBm
	31				
Operating & Storage Condition					
Operation Temperature Range: -40℃ ~ +85℃					
Storage Temperature Range: -65℃ ~ +150℃					


Yantel Corporation

Add: No.308-322, 3F, Building 1, Juchuang Jingu Innovation Park, Wenyuan Road 35, Xili Street, Nanshan, Shenzhen, China


Tel: 86-755-8355-1886 Fax: 86-755-8355-2533

For detailed performance specs & shopping online see Yantel web site : www.yantel-corp.com

Typical Performance (25°C: DC-6GHz)





Outline Drawing



COMMON DIMENSION & TOLERANCE			
S Y M B O L	ALL DIMENSION IN MILLIMETERS		
	MINIMUM	MOMINAL	MAXIMUM
A	0.70	0.75	0.80
A1	---	0.02	0.05
b	0.20	0.25	0.30
b1	0.20REF		
c	0.18	0.20	0.25
D	1.90	2.00	2.10
D1	1.50	1.60	1.70
e	0.50BSC		
E	1.90	2.00	2.10
E1	0.80	0.90	1.00
L	0.25	0.30	0.35
h	0.20	0.25	0.30

Simplified Schematic And Pad Description



Function	Pad Number	Description
RF-IN	2	RF-Input pad
RF-OUT	7	RF-Output pad
GND	1,8 & Paddle	Ground
NC	3-6	No connection, connected to ground externally

Characterization Test Circuit

